

**DIRECT CURRENT MOTOR CONDITION
MONITORING AND EXERCISING SYSTEM**

REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application 60/477,908 filed June 12, 2003.

BACKGROUND OF THE INVENTION

1. Technical Field:

[0002] The invention relates to the control and monitoring of electric motors and more particularly to a system providing exercising of and failure indicating for a direct current motor.

2. Description of the Problem:

[0003] Utility vehicles are often advantageously supplied with auxiliary equipment, the operation of which is supported by the vehicle. Such auxiliary equipment can include hydraulically powered, aerial lift platforms as are often used for the repair of electrical power distribution lines. Typically, a hydraulic lift platform will be driven by a primary pump which is in turn driven by the vehicle's engine. In some applications, a back up hydraulic system is provided having a pump powered by a direct current motor energized by the vehicle's battery.

[0004] Back up direct current motors fail more often than they should due to harsh operating environments and infrequent use. Failures of the motors can stem from corrosion between the motor brushes and commutator or from motor bearings seizing. It would be desirable to provide operators of utility vehicles indication of the status of these motors and improve the reliability by limiting the problems caused by lack of regular use.

SUMMARY OF THE INVENTION

[0005] According to the invention there is provided a motor vehicle having an engine and a direct current electrical power system. Vehicle accessory control is provided by a first controller area network including a remote power module. The remote power module includes a three state input and a control signal output. A direct current motor is connectable to the direct current electrical system for energization. A motor control switch connected by one terminal to the direct current electrical power system provides the usual method for energizing the direct current motor through the agency of an energization relay. This energization relay is exploited to provide for automated testing and exercise of the motor by the remote power module. The energization relay has an input terminal connected both to the control signal output of the remote power module and to a second terminal for the motor control switch. The power output terminal for the relay is connected to the direct current motor and to the three state input of the remote power module. Voltage levels appearing on the three state input (which is biased to first elevated voltage) indicate normal operation or failure. Periodic, momentary application of a control signal by the remote power module exercises the motor to prevent bearing seizure and to clean brushes and commutators.

[0006] Additional effects, features and advantages will be apparent in the written description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

[0008] **FIG. 1** is a simplified illustration of a truck mounted aerial lift assembly for locating an operator in various raised positions.

[0009] Fig. 2 is a high level schematic of a vehicle electrical and hydraulic control system incorporating the invention for the truck of Fig. 1.

[0010] Fig. 3 is a schematic of a remote power module and an emergency pump motor energization relay used in a preferred embodiment of the invention.

[0011] Fig. 4 is a flow chart of a program executed by a vehicle body controller to implement the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0012] Referring to the drawings, and particularly to FIG. 1, an example of a mobile aerial lift unit is illustrated in simplified presentation for clarity of illustration. The mobile aerial lift apparatus includes a truck 1 with an aerial lift unit 2 mounted to the bed thereof. The aerial lift unit 2 includes a lower boom 3 and an upper boom 4 pivotally interconnected to each other and to the truck bed through support 6 and rotatable support bracket 7. A basket 5 is shown secured to the outer end of the upper boom 4 within which the operating personnel are located during the lifting to and locating within a selected work area in accordance with known practice. Basket 5 is typically pivotally attached to the out end of the boom 4 to maintain a horizontal (level) orientation at all times. The aerial lift unit is mounted to the truck bed through support 6. A rotatable support bracket 7 is secured to the support 6 and projects upwardly. The lower boom 3 is pivotally connected as at pivot 8, to the rotatable support bracket 7. A lifting lower boom cylinder unit 9 is interconnected between bracket 7 and the lower boom 3. In the illustrated embodiment, a pivot connection 10 connects the lower boom cylinder 11 of unit 9 to the bracket 7. A cylinder rod 12 extends from the cylinder 11 and is pivotally connected to the boom 3 through a pivot 13. Lower boom cylinder unit 9 is connected to either of two supplies of a suitable pressurized hydraulic fluid, to lift and lower the assembly as desired.

[0013] The outer end of the lower boom 3 is interconnected to the lower and pivot end of the upper boom 4. A pivot 116 interconnects the outer end of the lower boom 3 to the pivot end of upper boom. An

upper boom/compensating cylinder unit or assembly **117** is connected between the lower boom **3** and the upper boom for pivoting the upper boom about pivot **116** for positioning of the upper boom relative to the lower boom. The upper boom/compensating cylinder unit **117** is constructed to permit independent movement of the upper boom **4** relative to lower boom **3** and to provide a compensating motion between the booms to maintain the upper boom raising with the lower boom and is similarly connected to the sources of pressurized hydraulic fluid. Conventionally, aerial lift unit **2** requires positive hydraulic pressure to support operation of lower boom cylinder **11** or the upper boom cylinder **117** for lifting or lowering.

[0014] Fig. 2 is a block diagram schematic illustrating electronic control of truck **1**, based on a controller area network technology and a body controller/computer **24**. Collectively, bus/data link **18** and the various nodes attached thereto form a public controller area network (CAN) conforming to the SAE J1939 standard. A second data link **19** also conforms to the SAE J1939 standard but is used for specialized signals relating to vehicle manufacturer specific accessories. Controller area networks are networks which do not have destination addresses for nodes attached to the networks, but rather provide for transmission of data in packets, identified as to the source, message type and priority. The nodes are programmed as to whether to respond to a packet based on one or more of the three identifiers. Many message types are predefined by the SAE J1939 standard. However, the SAE J1939 standard allows the definition of proprietary messages which conform in structure to the standard.

[0015] Active vehicle components are typically controlled by one of a group of autonomous, vocational controllers. The vocational controllers include a gauge cluster controller **14**, an engine controller **20**, a transmission controller **16**, and an antilock brake system (ABS) controller **22**. These controllers have publicly defined message types and are coupled to one another and with body controller/computer **24** by serial data bus **18**. The autonomous controllers communicating over serial data bus **18** include local data processing and programming and are typically supplied by the manufacturer of the controlled component. For each autonomous controller there is a defined set of variables used for communications between the autonomous controller and other data processing components coupled to the network. A body of warning lights **45**, under the direct control of gauge controller **14**, may be assigned to respond to as programmed into body controller **24**. This includes assigning a warning light to be activated upon a failure indication

from remote power module 36. Body controller 24 is programmed in certain circumstances to translate signals from one network to the other.

[0016] Remote power module (RPM) 36 is programmed to respond to body computer 24 commands relating to systems, typically electrical accessories, located on truck 1. In the present, preferred embodiment, RPM 36 is used to trip a relay 46 used to power a direct current motor 48 from the vehicle's battery 21. Control of an RPM 36 is then implemented in the body controller 24 and communicated to the RPM over a private data link 19. Remote power module 36 includes minimal processing power and operates essentially as a slave device to body computer 24. RPM 36 can be made independent.

[0017] The preferred application of the present invention is to monitor the condition of, and to exercise, an electrical motor 54 which provides a power to a back up/emergency pump 56 which in turn provides pressurized hydraulic fluid to an hydraulic system 58 such as may be used to lift and lower aerial lift unit 2. The primary system for energizing hydraulic system 58 is primary hydraulic pump 60, driven by engine 30. Should engine 30 fail, for example as a result of running out of fuel, stranding a suspended worker in an elevated basket 5, the vehicle's battery power may be used to power motor 54 and provide hydraulic drive fluid under pressure from pump 56 to hydraulic system 58 allowing the basket to be lowered. Electrical power for vehicle 11, and for the motor supported by RPM 36, can be supplied by one or more lead acid batteries 21, or by an alternator, which is part of charging system 47. Electrical power system 51 is supplied from batteries 21 upon moving a key switch (starter 53) from an off position to an accessory or on position, without cranking the vehicle engine 30, or from charging system 47 when the engine is running and driving the charging system 47.

[0018] Body controller 24 is connected by a SAE J1708 compliant serial data link to switch bank 48 and directly to discrete inputs 50, such as a on/off switch for hydraulic system 58. Body controller 24 also communicates with a discrete output section 52, which may control directly, or indirectly by way of relays, the various vehicle lamps.

[0019] Referring to Fig. 3, a remote power module 36 and its application to providing condition monitoring and exercising of an emergency electrical motor 54 is illustrated in greater detail. Remote power module 36 comprises a CAN transceiver circuit 68 and a microcontroller 66. Microcontroller 66 controls the switching state of a plurality of FET switches, one of which (FET switch 64) is shown, which may be used to provide 12 volt control signals on an output port. FET 64 cannot handle sufficient current to drive motor 54, so the FET is used instead to control the switching of a pump energization relay 46. The gate of FET switch 64 is controlled by microcontroller 66 and the output of FET switch 64 is coupled to a DIN 86 input of relay 46. RPM 36 has a 3 state input 84 coupled to one terminal of motor 54. Input 84 corresponds to node 71, the midpoint of a voltage divider circuit formed by resistors 70 and 72. Microcontroller 66 is coupled by an input terminal 186 to node 71 between resistors 70 and 72, which have relatively high resistances. Microcontroller 66 monitors the voltage at node 71 which provides an indication of the states of motor 54 brushes. Resistor 70 is connected between node 71 and an external source of accessory voltage suitable for establishing a first logic voltage level on node 71 for RPM 36. If motor 54 is not running, the voltage on node 71 will be pulled to ground by a short circuit drop through the (non-rotating) motor to ground. Insufficient current is supplied through resistor 70 to overcome the inertia of motor 54, with the result that the motor does not rotate. If the brush to commutator contacts are good, the motor will exhibit a negligible resistance. The current drawn through resistor 70 is a negligible drain on vehicle battery power. When motor 54 is not running microcontroller 66 should see a zero voltage on node 71. If the brushes or commutators of motor 54 are corroded and not conductive to electricity, the voltage on node 71 rises to a six volt drop across resistor 72 to ground, which is detected by microcontroller 66 and reported over data link 19 to body computer 24 using CAN controllers 68 and 76. Microcontroller 74 in body computer 24 interprets a six volt voltage on motor 54 as a failure indication, and instructs electronic gauge controller 14 over the public data link 18 using CAN controllers 78 and 80 to instruct microcontroller 82 to illuminate a light 45A designated to serve as a failure indicator.

[0020] Emergency pump motor 54 is normally energized by closure of a hard wired emergency pump control switch 62, which in turn applies 12 volts to the DIN 86 input of relay 46, closing the relay to close, and the motor to be energized directly from battery 21. Emergency pump relay is alternatively closed by sourcing the 12 volt control signal for DIN 86 from FET 64. This is effected by microcontroller 66 under

instruction from microcontroller **74**. In effect body computer **24** and remote power module **36** combine to provide a relay controller and motor input terminal voltage sensor. Energization of direct current motor **54** is done periodically and briefly to exercise motor **54**. This helps keep brushes and commutator contacts clean and helps prevent bearings from seizing. When relay **46** is closed, the voltage on node **71** should rise to **12** volts, allowing for a momentary drop in battery voltage when the load of turning motor **54** on is first imposed. The voltages occurring on node **71** are reported by microcontroller **66** to microcontroller **74**, and if they do not track expected values, microcontroller **74** issues the appropriate instruction to the electronic gauge cluster **14** to illuminate failure LED (light) **45A**. Failure of microcontroller **66** to see a rise in voltage or three state input **84** indicates failure, as may be associated with seized bearings.

[0021] Referring to **Fig. 4**, a flow chart illustrates the tests executed by microcontroller **74** for monitoring motor **54**. First, with the initial condition that motor **54** is not energized, the voltage on the 3 state input is read and compared to nominal values at step **90**. If the voltage is high, that is in the range of 6 volts, the program executes step **91** and instructs the gauge controller to illuminate a failure indicator light. If the voltage level is nominal, that is close to zero volts, it is determined if the time is appropriate to exercise (run) the motor. If not, the program loops back to sample the voltage level appearing on 3 state input **84** (after an appropriate delay). If yes, a gate control signal is applied to FET **64** (step **93**) for a brief period of time to briefly run motor **54**. Again the voltage appearing on the 3 state input is monitored and compared to expected values (step **94**). If the voltage fails to increase, typically to about the range of 12 volts, a failure is indicated and step **95** is executed to generate an instruction to indicate failure. If voltage does rise, operation is likely nominal and the program loops back to begin again.

[0022] The invention provides for monitoring and maintaining a brush DC motor. By applying a low power, operating voltage signal to the motor, problems with the brushes and commutators may be detected and indicated when the blocked rotor, short circuit path through the motor is interrupted and the trickle current supported by the voltage source is interrupted. A back up relay activation circuit allows the motor to be periodically exercised to prevent seizure of the motor bearings.

[0023] While the invention is shown in only one of its forms, it is not thus limited but is susceptible to various changes and modifications without departing from the spirit and scope of the invention.